



EXPLOSION-PROOF AIR CONDITIONERS

Horizontal Airflow Configuration

Model	Air		Voltage	MCA	Width	Length	Height	Weight
	Cool	Flow						
	BTUH	CFM	Volts/Phase/Hz	Amps	Inches	Inches	Inches	Net Lbs
PACX-H-020-1-B-***	24000	800	208-230/1/60	18	44.00	31.63	45.00	419
PACX-H-025-1-B-***	30000	1000	208-230/1/60	23	44.00	31.63	45.00	439
PACX-H-030-1-B-***	36000	1200	208-230/1/60	24	44.00	31.63	45.00	477
PACX-H-035-1-B-***	42000	1400	208-230/1/60	28	44.00	31.63	45.00	518
PACX-H-040-1-B-***	49900	1600	208-230/1/60	36	83.06	46.56	33.50	724
PACX-H-040-1-C-***	48900	1600	208-230/3/60	25	83.06	46.56	33.50	729
PACX-H-040-1-D-***	48900	1600	460/3/60	12	83.06	46.56	33.50	729
PACX-H-050-1-B-***	64000	2000	208-230/1/60	47	83.06	46.56	33.50	744
PACX-H-050-1-C-***	62500	2000	208-230/3/60	31	83.06	46.56	33.50	749
PACX-H-050-1-D-***	62500	2000	460/3/60	16	83.06	46.56	33.50	749
PACX-H-062-1-C-***	75000	2500	208-230/3/60	37	87.06	49.56	35.00	800
PACX-H-062-1-D-***	75000	2500	460/3/60	18	87.06	49.56	35.00	800
PACX-H-075-1-C-***	92000	3000	208-230/3/60	43	87.06	49.56	35.00	859
PACX-H-075-1-D-***	92000	3000	460/3/60	21	87.06	49.56	35.00	859
PACX-H-075-2-C-***	90000	3000	208-230/3/60	42	87.06	49.56	35.00	946
PACX-H-075-2-D-***	90000	3000	460/3/60	21	87.06	49.56	35.00	946
PACX-H-085-2-C-***	106000	3400	208-230/3/60	49	94.31	63.31	49.00	1235
PACX-H-085-2-D-***	106000	3400	460/3/60	29	94.31	63.31	49.00	1235
PACX-H-100-2-C-***	125000	4000	208-230/3/60	56	94.31	63.31	49.00	1280
PACX-H-100-2-D-***	125000	4000	460/3/60	30	94.31	63.31	49.00	1280
PACX-H-125-2-C-***	155000	5000	208-230/3/60	72	107.31	70.81	50.00	1615
PACX-H-125-2-D-***	155000	5000	460/3/60	32	107.31	70.81	50.00	1615
PACX-H-150-2-C-***	183000	6000	208-230/3/60	82	107.31	70.81	50.00	1640
PACX-H-150-2-D-***	183000	6000	460/3/60	37	107.31	70.81	50.00	1640
PACX-H-175-2-C-***	210000	7000	208-230/3/60	100	122.31	84.81	54.00	1965
PACX-H-175-2-D-***	210000	7000	460/3/60	47	122.31	84.81	54.00	1965
PACX-H-200-2-C-***	246000	8000	208-230/3/60	123	122.31	84.81	54.00	2090
PACX-H-200-2-D-***	246000	8000	460/3/60	53	122.31	84.81	54.00	2090
PACX-H-250-2-C-***	290000	10000	208-230/3/60	132	122.31	84.81	54.00	2200
PACX-H-250-2-D-***	290000	10000	460/3/60	57	122.31	84.81	54.00	2200
PACX-H-275-2-C-***	330000	11000	208-230/3/60	156	180.31	90.06	70.44	3872
PACX-H-275-2-D-***	330000	11000	460/3/60	70	180.31	90.06	70.44	3872
PACX-H-300-2-C-***	360000	12000	208-230/3/60	177	180.31	90.06	70.44	3960
PACX-H-300-2-D-***	360000	12000	460/3/60	79	180.31	90.06	70.44	3960
PACX-H-350-2-C-***	420000	14000	208-230/3/60	182	180.31	90.06	70.44	4046
PACX-H-350-2-D-***	420000	14000	460/3/60	82	180.31	90.06	70.44	4046
PACX-H-400-2-C-***	480000	16000	208-230/3/60	243	232.94	90.06	77.00	5102
PACX-H-400-2-D-***	480000	16000	460/3/60	110	232.94	90.06	77.00	5102
PACX-H-490-2-C-***	587000	20000	208-230/3/60	277	232.94	90.06	77.00	5322
PACX-H-490-2-D-***	587000	20000	460/3/60	125	232.94	90.06	77.00	5322

